

Continuation

General Data

Capacitance	100 VDC/63 VAC*				250 VDC/180 VAC*				400 VDC/250 VAC*				630 VDC/400 VAC*			
	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**	W	H	L	PCM**
1000 pF	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5**
1500 "	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5**
2200 "	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5**
3300 "	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5	4	9	10	7.5**
4700 "	3	8.5	10	7.5	3	8.5	10	7.5	3	8.5	10	7.5	4	9	10	7.5**
6800 "	3	8.5	10	7.5	3	8.5	10	7.5	4	9	10	7.5	4	9	10	7.5**
													4	9	13	10*
0.01 µF	3	8.5	10	7.5	3	8.5	10	7.5*	4	9	10	7.5*	5	10.5	10.3	7.5**
					4	9	13	10*	4	9	13	10*	4	9	13	10*
0.015 "	3	8.5	10	7.5	4	9	10	7.5*	5	10.5	10.3	7.5*	5	11	13	10*
					4	9	13	10*	4	9	13	10*	5	11	18	15*
0.022 "	4	9	10	7.5	4	9	10	7.5*	5	10.5	10.3	7.5*	5	11	13	10*
					4	9	13	10*	4	9	13	10*	5	11	18	15*
0.033 "	4	9	13	10	5	10.5	10.3	7.5*	5.7	12.5	10.3	7.5*	6	12	13	10*
					4	9	13	10*	5	11	13	10*	5	11	18	15*
0.047 "	4	9	13	10	5	10.5	10.3	7.5*	6	12	13	10*	6	12.5	18	15*
					4	9	13	10*	5	11	18	15*	6	15	26.5	22.5*
0.068 "	5	11	13	10	5	11	13	10*	6	12.5	18	15*	7	14	18	15*
					5	11	18	15*	6	15	26.5	22.5*	6	15	26.5	22.5*
0.1 µF	6	12	13	10	6	12	13	10*	7	14	18	15*	9	16	18	15*
					5	11	18	15*	6	15	26.5	22.5*	7	16.5	26.5	22.5*
0.15 "	6	12.5	18	15	6	12.5	18	15*	8	15	18	15*	8.5	18.5	26.5	22.5*
					6	15	26.5	22.5*	6	15	26.5	22.5*	9	19	31.5	27.5*
0.22 "	7	14	18	15	7	14	18	15*	9	16	18	15*	8.5	18.5	26.5	22.5*
					6	15	26.5	22.5*	7	16.5	26.5	22.5*	9	19	31.5	27.5*
0.33 "	8	15	18	15	8	15	18	15*	8.5	18.5	26.5	22.5*	11	21	26.5	22.5*
					6	15	26.5	22.5*	9	19	31.5	27.5*	11	21	31.5	27.5*
0.47 "	7	16.5	26.5	22.5	9	16	18	15*	10.5	19	26.5	22.5*	11	21	31.5	27.5
					7	16.5	26.5	22.5*	9	19	31.5	27.5*				
0.68 "	8.5	18.5	26.5	22.5	8.5	18.5	26.5	22.5*	11	21	26.5	22.5*	15	26	31.5	27.5*
					9	19	31.5	27.5*	11	21	31.5	27.5*	13	24	41.5	37.5*
1.0 µF	10.5	19	26.5	22.5	11	21	26.5	22.5*	13	24	31.5	27.5*	17	29	31.5	27.5*
					11	21	31.5	27.5*	13	24	41.5	37.5*	15	26	41.5	37.5*
1.5 "	11	21	31.5	27.5	13	24	31.5	27.5*	17	29	31.5	27.5*	20	39.5	31.5	27.5*
					13	24	41.5	37.5*	13	24	41.5	37.5*	19	32	41.5	37.5*
2.2 "	13	24	31.5	27.5	15	26	31.5	27.5*	20	39.5	31.5	27.5*	20	39.5	41.5	37.5
					13	24	41.5	37.5*	17	29	41.5	37.5*				
3.3 "	17	29	31.5	27.5	17	34.5	31.5	27.5*	20	39.5	41.5	37.5	24	45.5	41.5	37.5
					17	29	41.5	37.5*								
4.7 "	17	29	41.5	37.5	20	39.5	31.5	27.5*	20	39.5	41.5	37.5				
					19	32	41.5	37.5*								
6.8 "	19	32	41.5	37.5	20	39.5	41.5	37.5	24	45.5	41.5	37.5				
10 µF	20	39.5	41.5	37.5	24	45.5	41.5	37.5								
15 "	24	45.5	41.5	37.5												

* AC voltage: $f \leq 1000 \text{ Hz}$; $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

** PCM = Printed circuit module = lead spacing

■ New values and box sizes.

* On ordering please state the required PCM (lead spacing)!

If not specified, smaller PCM will be booked.

** Admissible AC voltage 280 VAC max.

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible AC voltage.

Taped version see page 100.

Rights reserved to amend design data without prior notification.

∅ d	PCM	W
0.5	7.5	= 3
0.7	7.5	≥ 4
0.7	10	
0.8	15 - 22.5	
0.8	27.5	≤ 15
1.0	27.5	> 15
1.0	37.5	

